

HERACLES



code 2000/2100/2200/2300

Specifications

Heracles 2000

yoke mount with 5/8" (16mm) socket
200W AC 90-260V kg.1,086

Heracles 2100

yoke mount with 5/8" (16mm) socket
125W AC 90-260V kg.1,086

Heracles 2200

Hand grip with 3/8" thread
200W DC 20-36V kg.1,118

Heracles 2300

Hand grip with 3/8" thread
125W DC 20-36V kg.1,118

Lightweight construction in aluminum.
Front radiator housing.
Spot/flood rear ergonomic lever.
Integral safety glass.
Instant hot restrike igniter.
Extra-pure polished aluminium reflector.
Epoxy anti-scratch finish.
Lamp type HMI/MSR (5600°k) 125/200W Lampholder: GY 9,5.

Accessories

Code 2001: 110 gr. Four leaf barndoor + gel clips
Code 2002: 90 gr. Dichroic orange CTO filter
Code 2003: 90 gr. Diffuser glass
Code PHO WD: small White dome
Code 161: 320 gr. Umbrella ø 80 cm.
Code M026: 350 gr. Umbrella universal adapter lite-tite
Code 106: Mini Pro Alu stand (Minipro 051N)
Code 327: Gag grip with 5/8" (16mm) spigot

Photometrics

DISTANCE 5m	SPOT	FLOOD
light center value	1237	424
beam angle= beam at 50% peak value	24°	51°
field angle= beam at 10% peak value	50°	94°
RATIO	1:2,92	

(Fitting lamp type 200W DAYLIGHT MSR 200 HR 5600°K)



CODE 2200/2300

POWER SYSTEM

(See the specifications in the dedicate leafleft)



Cod. 2150: AC Ballast 125/200W



Cod. 2350: Dual ballast DC 125/200W



Cod. 2800: Battery Belt 30V NiM



Cod. 2400: Battery Pack 30V



Cod. 2600: Silver Charger



CODE 2000/2100